



# HiTEC<sup>®</sup> 2235

## *Two-Stroke Additive Package*

### Application

HiTEC<sup>®</sup> 2235 additive is a low-ash multifunctional additive for air-cooled two-stroke engine oils. HiTEC<sup>®</sup> 2235 additive has been developed to meet the latest performance requirements including JASO FC, ISO EGC & EGD and Thailand Industrial Standards Institute (T.I.S.I. 1040).

### Recommended Dosage

Recommended dosages for HiTEC<sup>®</sup> 2235 additive are:

- 3.0% weight for JASO FB & ISO EGB performance
- 3.8% weight for API TC, JASO FC, ISO EGC and T.I.S.I. 1040 performance
- 7.5% weight adds ISO EGD performance

Contact your Afton Chemical representative for specific recommendations.

### Features

- Strong detergent performance
- Increased protection from piston seizure, ring sticking, engine deposits and exhaust blocking
- Ability to be used with a wide variety of basestock systems

### Typical Characteristics

Appearance	Dark brown viscous liquid
Density @ 15°C, g/ml	0.93
Viscosity @ 100°C, mm	170
Flash Point (PMC), °C	155
Calcium, % wt.	0.70
TBN, mg KOH/g	44
Specific Gravity @ 15.6/15.6°C	0.935

### Storage, Handling & Toxicity

Maximum storage temp.: 50°C

Recommended handling temp.: 55-60°C

Maximum handling temp.: (<24 hrs): 70°C

Maximum blending temp.: 70°C

Shelf Life: 36 months @ ambient (10-30°C)

For specific safety, handling and toxicity information, please refer to the current Material Safety Data Sheet or call 1-800-325-7079.

The information in this bulletin is, to our best knowledge, correct and accurate, but all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Afton Chemical Corporation and its subsidiaries disclaim any liability incurred in connection with the use of these data or suggestions. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use. HiTEC(R) is a registered trademark of Afton Chemical Corporation. [www.aftonchemical.com](http://www.aftonchemical.com)