



POLYPOX IPD

PROPERTIES

- cycloaliphatic diamine

SPECIFICATIONS*

parameter	unit	figure	method
amine number	mg KOH/g	660 ± 15	UPPC-16945
viscosity, 25 °C, P/K	mPa·s	15 ± 10	UPPC-53018-1
colour number	Gardner	≤ 1	UPPC-4630

* valid at the time of print; You receive the topical specifications on request.

TECHNICAL DATA

parameter	unit	figure	method
H-equivalent	g/equivalent	43	

PHYSIOLOGY

While dealing with epoxy resins and curing agents, please consider the safety precautions mentioned in the risk and safety phrases. Avoid pollution of the unprotected skin - wash off with warm water and soap, if necessary. Wear protective clothing and use barrier cream before starting your work, please!
Always ensure that all health and safety procedures are in accordance with local and national Government requirements.

PACKAGE

POLYPOX IPD is available in drums of 200 kg net each. Other sizes on request.

STORAGE LIFE

POLYPOX IPD is at least 12 months stable in the original can.

TECHNICAL DATA SHEET

POLYPOX IPD

Any technical recommendations given by us whether orally or in writing are not binding on us, also with regard to any rights of third parties. Prospective users should conduct their own trials to determine whether our products are suitable for the intended purpose. Our liability is governed by our general conditions of sale.

10-2008

page 1 of 2



DOW
EPOXY
SYSTEMS



Keep cool and dry.

TECHNICAL DATA SHEET

POLYPOX IPD

Any technical recommendations given by us whether orally or in writing are not binding on us, also with regard to any rights of third parties. Prospective users should conduct their own trials to determine whether our products are suitable for the intended purpose. Our liability is governed by our general conditions of sale.

08-2008

page 2 of 2

UPPC GmbH
Tel: (+49) 7356/9355-0

Schemmerberger Str. 39
Fax: (+49) 7356/9355-16

D-88487 Mietingen-Baltringen
e-mail: uppc@uppc.de